

Application No. 09/612,829
Response to the Office Action Mailed July 5, 2005
Amendment dated October 5, 2005

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-13. (Canceled)

14. (Currently amended) A method for handling a plurality of samples in a multi-channel capillary electrophoresis apparatus comprising:

providing a plurality of samples located on a work surface, with each sample at a respective work surface coordinate ~~wherein the temperature of the work surface is controlled by a temperature controller~~

transferring simultaneously ~~transferring~~ at least two of the samples from their respective work surface coordinates to respective loading wells not located on the work surface, wherein each loading well includes a capillary fixedly positioned therein and wherein a one-to-one correspondence between a work surface coordinate and a loading well is not required; and

injecting the samples from the loading wells into the capillaries.

15. (Previously presented) The method of claim 14, wherein each work surface coordinate is defined by a respective sample well.

16. (Previously presented) The method of claim 14 wherein the loading well is located in a sample loading assembly.

17. (Previously presented) The method of claim 14 wherein the injecting is performed by electrokinetic injection.

Application No. 09/612,829
Response to the Office Action Mailed July 5, 2005
Amendment dated October 5, 2005

18. (Previously presented) The method of claim 14 further comprising controlling the humidity of the environment surrounding the work surface to reduce sample evaporation.

19. (Canceled)

20. (Previously presented) The method of claim 15 wherein each sample well is a well of a conventional multi-well plate comprising 96, 384 or 1536 wells arranged in a rectangular array.

21. (Previously presented) The method of claim 14 wherein the capillary is a capillary tube.

22. (Canceled)

23. (Previously presented) The method of claim 14 wherein the simultaneously transferring includes decoupling a spatial arrangement of the work surface coordinates from a spatial arrangement of inlets of the capillaries positioned in the loading wells.

24. (Currently amended) A method for handling a plurality of samples in a multi-channel capillary electrophoresis apparatus comprising:

providing a plurality of samples located on a work surface, with each sample at a respective work surface coordinate, ~~wherein the temperature of the work surface is controlled by a temperature controller;~~

aspirating at least two of the samples into at least two respective pipettes;

transferring simultaneously ~~transferring the~~ at least two samples from their respective work surface coordinates, in the at least two respective pipettes, to at least two respective loading wells not located on the work surface, wherein each of the at least two loading wells includes a capillary fixedly positioned therein and wherein a one-to-one correspondence between a work surface coordinate and a loading well is not required, and the simultaneously transferring

Application No. 09/612,829
Response to the Office Action Mailed July 5, 2005
Amendment dated October 5, 2005

comprises ejecting the at least two samples out of the at least two respective pipettes into the at least two respective loading wells; and

injecting the samples from the at least two loading wells into the capillaries.

25. (Canceled)

26. (Previously presented) The method of claim 24 wherein the simultaneously transferring includes decoupling a spatial arrangement of the work surface coordinates from a spatial arrangement of inlets of the capillaries positioned in the loading wells.

27. (New) A method for handling a plurality of samples in a multi-channel capillary electrophoresis apparatus, comprising:

providing a plurality of samples located on a work surface, with each sample at a respective work surface coordinate;

transferring simultaneously at least two of the samples from their respective work surface coordinates to respective loading wells not located on the work surface, wherein each loading well is in fluid communication with a respective capillary formed in a monolithic substrate, and each respective capillary comprises a capillary of a multi-channel capillary electrophoresis apparatus; and

injecting the samples from the loading wells into the capillaries.

28. (New) The method of claim 27, wherein a one to one correspondence between the work surface coordinates and the capillaries is not required.

29. (New) The method of claim 27, wherein each respective capillary comprises a respective inlet.

Application No. 09/612,829
Response to the Office Action Mailed July 5, 2005
Amendment dated October 5, 2005

30. (New) The method of claim 29, wherein a spatial arrangement of sample wells is decoupled from a spatial arrangement of the capillary inlets.

31. (New) The method of claim 27, wherein there is no relative motion between each respective capillary and the loading well.